

# JALARCHER SAS

## JJV28



**S3 CI HI HRO SRC**  
**EN ISO 20345:2011**  
**38 to 47**



- Water-repellent full-grain leather
- Sole **Vibram® J-ESCAPE**
- Polymer toe cap type B and midsole no metallic
- Antistatic

- ❖ Ranger type boot, black colour.
- ❖ Bootstrap in water-repellent full grain leather, 1,9 / 2,1 mm thick. Anti-abrasion heel protection and reflecting insert for improved visibility.
- ❖ Ergonomic padded collar and padded ankle protector.
- ❖ Anti-abrasion PU scuff cap. YKK water proof zip for quick release with velcro protection.
- ❖ Upper lined in breathable **3D Surf** mesh with honeycomb structure to improve the peripheral ventilation of the foot, dries out rapidly.
- ❖ Padded tongue for good instep protection, combined with two side bellows to prevent any dirt from getting into the boots.
- ❖ YKK water-proof zip for quick release with velcro protection.
- ❖ **Soft** footbed made of **BASF Dynamic polyurethane** with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical, breathable and fitted
- ❖ Ergonomic shoe with **broad synthetic polymer toe cap type B**, for saving on weight (50% lighter than steel) Impact resistance to **200 Joules**. Minimum height after test  $\geq 4\text{mm}$  in relation to the Type A toe cap in accordance with Standard 22568-2:2019.
- ❖ **FleXtane™** By Jallatte anti-perforation inner sole and insert 100 % composite, yielding and flexible, non-detectable, non-magnetic and 70 % lighter than steel. Directly sewn to the bootstrap for 100% protection of the whole surface of the foot. 100% composite materials: lighter than steel, amagnetic, non-conductive of heat and cold.
- ❖ Heel stiffener to reinforce the heel seat.
- ❖ **Sole J-ESCAPE™ VIBRAM CA/PU** with **progressive effect shock-absorber** to protect the back and joints from vibrations . Pu reinforcement to the front of the sole.

### Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

**Requirement SRC (SRA+SRB)**

**SRA** Test ground : ceramic / lubricant : water and detergent

On flat **0,40** (>0,32) – On the heel **0,32** (>0,28)

**SRB** Test ground steel / lubricant : glycerine

On flat **0,21** (>0,18) – On the heel **0,16** (>0,13)

- **Softane™** comfort layer
- Density = 0.45. Ensures comfortable walking for the wearer. Helps to absorb vibrations and provided heat insulation to the sole of the foot.
- Ground contact layer in **Néotril™** :
- Very highly resistant to oils, greases and conducted heat (300°C)
- Highly scuff- resistant.
- Sole very resistant to hydrocarbons.



|                |  |
|----------------|--|
| Weight         | Gross weight(42) : 1748 g / Net weight (42) : 1530 g |
| Size           | 38 to 47   |
| Packaging      | 5 pairs  |
| Box shoes (mm) | 337 x 328 x 135                                      |
| Cartons (mm)   | 625 x 425 x 345                                      |